

HMM213 Humidity Measurement Module

Humidity measurement module		HMM213	R	R		A				R	R		PRICE
Output	only RS232 serial output		R	R									
Humidity probe length	90 mm <i>215 mm</i>				1								
Sensor protection	sintered stainless steel filter (HM46670)					A							
Humidity probe cable length **)	0.65 m <i>1.5 m</i> <i>3.0 m</i>						1						
Output parameters	RH + T -probe <i>- with sensor regaining warmed probe *)</i> <i>- with sensor regaining warmed probe *) and additional T-probe</i> <i>- with sensor regaining</i>	RH + T <i>RH + T</i> <i>Td</i> <i>RH + T</i> <i>RH + T</i>						A					
Additional temperature probe	no T-probe <i>1.5 m cable</i> <i>3.0 m cable</i>	<i>(Select this if output parameter is A,B,C or D)</i> <i>(Available only if output parameter is E or F,</i> <i>(Available only if output parameter is E or F)</i>							1				
Manual	no manual english												
												A	
												B	
												TOTAL	
												QTY	
												TOTAL VALUE	

*) If the warmed humidity probe is selected, the humidity probe length must be 90 mm

**) Cable lengths specified for 90 mm probe; in case of 215 mm probe the lengths are reduced by 0.125 m.

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

HMM213	R	R	1	A	1	A	1	R	R	B
--------	---	---	---	---	---	---	---	---	---	---

End customer: _____