

# Vaisala Air Quality Monitoring System AQM60



## Benefits

- Site-specific air quality monitoring
- Air quality, weather and traffic data collected at one site
- Safer traveling environment for motorists
- Provides data for mitigation and control of pollutant levels
- Alert the public about poor air quality
- Cost-effective

## Features

- Configure the system with up to six sensors to meet your needs
- Optional noise sensor
- Rapid real-time data sampling (2-minute)
- Large data storage capacity (>15 years)
- Data available in Vaisala software
- Modular design enables easy maintenance
- Remote diagnostic capabilities
- Weatherproof and compact enclosures

## Overview

Air pollutants can be harmful to public health and the environment, especially near roadways where vehicles emit gases continually in a localized area. Monitoring air quality data near roadways can assist with pollution mapping and control; detecting emissions from traffic flow, in tunnels, and near construction projects; environmental impact assessments, urban land use planning and community health programs (alerting the public about poor air quality). The Vaisala Air Quality Monitoring System AQM60 is a complete air quality monitoring system designed to measure a wide range of air quality parameters in a cost-effective, compact package.

The Vaisala Air Quality Monitoring System AQM60 system measures many of the pollutants considered harmful by the EPA (Environmental Protection Agency) including: Nitrogen Dioxide (NO<sub>2</sub>); Ozone (O<sub>3</sub>); Carbon Monoxide (CO); Carbon Dioxide (CO<sub>2</sub>); and Particulate Matter (PM<sub>2.5</sub> and PM<sub>10</sub>). The Vaisala Air Quality Monitoring System AQM60 integrates with RWIS (Road Weather Information System), advisory radio systems, and ITS software platforms to provide weather, traffic and air quality data on one system. This allows customers to not only mitigate and control pollutant levels, but also save costs by combining their weather and traffic monitoring with the air quality system.

# Technical data

## Sensors (most common)

NO<sub>2</sub>; O<sub>3</sub>; CO; CO<sub>2</sub>; VOC; PM<sub>2.5</sub> and PM<sub>10</sub>

## Other Sensor Options

Noise and SO<sub>2</sub>

## Environmental Operating Range

-20 °C to 60 °C (-4 °F to 140 °F)  
with appropriate Thermal Management System (TMS)\*  
10 to 90 %RH (non condensing)

## Power Requirements

12VDC (power subject to configuration)  
AC power module 100 - 240 VAC

## Maintenance Checks Routine

3, 6 or 12 months (site dependent)

## Approvals

Electrical Safety and Conformity: CE; UL E215312  
Gas Sensors: EN50082-1:1997; EN50081-1:1992; Part 15 FCC Rules;  
IPCA 610D Class 2  
Particle Monitor: Class 1 laser; IEC 60825-1:1998

## Environmental Operating Range

-40 °C to 60 °C (-4 °F to 140 °F)  
with appropriate Thermal Management System (TMS)\*  
10 to 90 %RH (non condensing)

## Applications

- Urban and remote roadways
- Traffic flow control
- Identification of air quality trouble spots
- Tunnel monitoring
- Airports (noise detection can be included)
- Before /after road construction or mitigation strategies
- Long term air quality trend analysis
- Short term environmental impact assessments
- Local community exposures: residential, schools, pedestrians, shopping centers

## Sensor Modules\*\*

GAS	RANGE	ACCURACY
Nitrogen Dioxide (NO <sub>2</sub> )	0 - 0.2 ppm	± 0.010 ppm
Ozone (O <sub>3</sub> )	0 - 0.15 ppm	± 0.005 ppm
Carbon Monoxide (CO)	0 - 25 ppm	± 1 ppm
Carbon Dioxide (CO <sub>2</sub> )	0 - 2000 ppm	< 40 ppm + 3 %
Volatile Organic Compounds (VOC)	0 - 25 ppm	± 10 %
Particulate Matter (PM <sub>2.5</sub> and PM <sub>10</sub> )	0 - 2000 µg/m <sup>3</sup>	8 % of NIOSH 0600

\* TMS is customized for the sensor configuration and the environmental conditions at each location.

\*\* Other sensor modules available upon request.

# VAISALA

For more information, visit  
[www.vaisala.com](http://www.vaisala.com) or contact  
us at [sales@vaisala.com](mailto:sales@vaisala.com)

Ref. B211062EN-A ©Vaisala 2010  
This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

