



Order form  
Purchaser

Valid from September 2011  
Order no

## Vaisala Temperature Probe HMP110T

Vaisala Temperature Probe		HMP110T							PRICE
1	Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4..20 mA converter (channel 1 only) RS485 Interface for Vaisala devices (VDIGI)	A B C D I R V						
2	Analog output range	RS485 or VDIGI -40 ... +60 °C -40 ... +80 °C		0 2 5					
3	Sensor protection	Plastic grid with filter <i>Plastic grid</i> <i>Stainless steel sintered filter</i>			A B C				
4	Accessories	<b>No accessories</b> Pair of plastic nuts Probe holder for Vaisala products <i>Duct installation kit</i> 215619		0 1 2 3					
5	Probe cable length	<b>No cable</b> <i>60 °C cable 0.3 m</i> HMP50Z032 <i>60 °C cable 3 m</i> HMP50Z30A <i>High temperature cable 1.5 m</i> <i>High temperature cable 3 m</i> <i>180 °C FEP cable 3m</i> 226902				1 2 3 4 5 F			
6	User guide	<b>No user guide</b> <b>Multilingual quick guide</b>					A B		
7	Loop power converter	<b>No converter</b> <i>4...20 mA loop power converter</i>		0 1					
TOTAL									
QTY									
TOTAL VALUE									

Selections in bold are included in the prices of the basic versions.  
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP110T	V	0	B	2	1	A	0
---------	---	---	---	---	---	---	---