VAISALA

Order form
Orderer

Valid from 16.06.2006
Order no.

CL31 Lidar Ceilometer

Vaisala Ceilometer		**CL31**		**B**	**1**		**1**			**A**							**1**		PRICE
Operating voltage	**100-115 VAC**		**1**																
	230 VAC		**2**																
Reserved				**B**															
Reserved					**1**														
Data line interface	**RS232**					**A**													
	RS485					B													
	Modem (DMX501 modem module)					*C*													
Reserved							**1**												
Software	**Standard**							**A**											
	Standard + Sky Condition							*B*											
Cable Termination Box	**No**								**1**										
	Box with additional transient protection (Termbox-1200)								2										
	Box without additional transient protection (CLTERMBOX)								*3*										
Reserved										**A**									
Optical Termination Hood	**No**										**1**								
	Needed for indoor service (CLTERMHOOD)										*2*								
Service Cable	**No**											**A**							
	RS cable for local maintenance access (QMZ101)											*B*							
CL-View	**No**												**1**						
	PC User Interface Software for Ceilometers												*2*						
Shock Absorber	**No**													**A**					
	CT35022, recommended for marine and off-shore installations													*B*					
Internal Humidity Transmitter	**No**														**1**				
	HMP50 UAB1A1A humidity transmitter														*2*				
Radio Modem Kit	**No**															**A**			
	Attachment mechanics for radio antenna (CLRADIOKIT)															*B*			
Reserved																	**1**		
Manual language	**No manual**																	**A**	
	English																	B	
																	TOTAL		
																	QTY		
																	TOTAL VALUE		

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

CL31	**2**	**B**	**1**	**A**	**1**	**A**	**2**	**A**	**1**	**B**	**1**	**A**	**1**	**A**	**1**	**B**

End customer: _____