

HMP5 Humidity and Temperature Probe for High Temperatures



8UREHERGIDOOHISUREHEIDGEHEHOOEHII
SUREHIDBI □

Features/Benefits:

- Relative Humidity accuracy up to ± 0.8 %RH
- Temperature measurement range $-70 \dots +180$ °C ($-94 \dots +356$ °F)
- Vaisala HUMICAP®R2 sensor for superior accuracy and □ stability
- Excellent performance in harsh conditions; good chemical □ tolerance
- Corrosion-resistant IP66 probe housing
- Traceable calibration (certificate included)
- Modbus RTU over RS-485
-
-
-
- Humidity parameter options: Relative humidity, □ temperature, dew point temperature, wet-bulb temperature, □ absolute humidity, mixing ratio, water concentration, water □ mass fraction, water vapor pressure, enthalpy
- Compatible with Vaisala’s INSIGHT software

Summary:

Probe shall incorporate a thin film polymer capacitive HUMICAP®R2 humidity sensor with accuracy of ± 0.8 %RH ($0 \dots 90$ %RH) at $+23$ °C ($+73.4$ °F). Temperature sensor shall be a platinum 100Ω RTD with accuracy up to 0.1 °C (0.18 °F) at $+23$ °C ($+73.4$ °F). Electronics to be protected in an IP66 rated metal probe body with an operating temperature range of $-40 \dots +80$ °C ($-40 \dots +176$ °F). Probe to be powered by $15 \dots 30$ VDC with Modbus RTU communication protocol over RS-485. Remote probe shall have a temperature operating range of $-70 \dots +180$ °C ($-94 \dots +356$ °F), with relative humidity accuracy specified between $-40 \dots +180$ °C ($-40 \dots +356$ °F). Standard cable length 2 meters (optional 1, 3, 5, 10 meter extension cables). Probe shall calculate and directly output dew point temperature, wet-bulb temperature, absolute humidity, mixing ratio, water concentration, water mass fraction, water vapor pressure, and enthalpy. Probe shall have the ability to be calibrated in the field via PC connection. Traceable calibration certificate included.