

## 産業用キャビネット CAB100

項目	1	2	3	4	5	6	7	8	9	10	11	12	13	
産業用キャビネット(PDT101モデル)	CAB100	B	1	N	0	N	0		A	N		N		
1 キャビネットサイズ 大型	600 x 500 x 200	B												
2 電源 供給電源	DINレール24VDC/2.5A		1	N	0	N	0							
7 差圧 +/-60Pa, 電流	なし						0							
	PDT101-P4C x 1						1							
	PDT101-P4C x 2						2							
	PDT101-P4C x 3						3							
	PDT101-P4C x 4						4							
	PDT101-P4C x 5						5							
	PDT101-P4C x 6						6							
	PDT101-P4C x 7						7							
	PDT101-P4C x 8						8							
	PDT101-P4C x 9						9							
	PDT101-P4C x 10						A							
	PDT101-P4C x 11						B							
	PDT101-P4C x 12						C							
8 差圧 +/- 0.25" H2O,電流	なし							N						
	PDT101-W4C x 1							A						
	PDT101-W4C x 2							B						
	PDT101-W4C x 3							C						
	PDT101-W4C x 4							D						
	PDT101-W4C x 5							E						
	PDT101-W4C x 6							F						
	PDT101-W4C x 7							G						
	PDT101-W4C x 8							H						
	PDT101-W4C x 9							J						
	PDT101-W4C x 10							K						
	PDT101-W4C x 11							L						
	PDT101-W4C x 12							M						
9 通信 ポートサーバー x 1	DIGI Port Server TS4							A						
10 イーサネットスイッチ なし									0					
	あり	2+4 PoE IEEE 802.3af/at							1	N				
12 底部フランジ材質 ゴムフランジ	ケーブルクランプバー付きマルチゲートMC25 x 2									1				
	金属フランジ	ニッケルメッキ真鍮EMCケーブルグランド付きステンレス x 2								2	N			