

## 産業用キャビネット CAB100

項目		1	2	3	4	5	6	7	8	9	10	11	12	13	
	産業用キャビネット(PDT101モデル)	CAB100						B	1	N	0	N	0		
1	キャビネットサイズ	大型	600 x 500 x 200					B							
2	電源	供給電源	DINレール24VDC/2.5A					1	N	0	N	0			
7	差圧 +/-60Pa, 電流	なし						0							
		PDT101-P4C x 1						1							
		PDT101-P4C x 2						2							
		PDT101-P4C x 3						3							
		PDT101-P4C x 4						4							
		PDT101-P4C x 5						5							
		PDT101-P4C x 6						6							
		PDT101-P4C x 7						7							
		PDT101-P4C x 8						8							
		PDT101-P4C x 9						9							
		PDT101-P4C x 10						A							
		PDT101-P4C x 11						B							
		PDT101-P4C x 12						C							
8	差圧 +/- 0.25" H2O, 電流	なし						N							
		PDT101-W4C x 1						A							
		PDT101-W4C x 2						B							
		PDT101-W4C x 3						C							
		PDT101-W4C x 4						D							
		PDT101-W4C x 5						E							
		PDT101-W4C x 6						F							
		PDT101-W4C x 7						G							
		PDT101-W4C x 8						H							
		PDT101-W4C x 9						J							
		PDT101-W4C x 10						K							
		PDT101-W4C x 11						L							
12		PDT101-W4C x 12						M							
9	通信	ポートサーバー x 1	DIGI Port Server TS4							A					
10	イーサネットスイッチ	なし								0					
		あり	2+4 PoE IEEE 802.3af/at							1	N				
12	底部フランジ材質	ゴムフランジ	ケーブルクランプパー付きマルチゲートMC25 x 2										1		
		金属フランジ	ニッケルメッキ真鍮EMCケーブルグランド付きステンレス x 2										2	N	