

GMP252 Carbon Dioxide Probe for ppm-level measurements

		1	2	3	4	5	6	7	8	PRICE
Vaisala CARBOCAP® Carbon Dioxide Probe GMP252										
Probe options and settings	1 Probe type / Analog	0...10 000 ppm with porous sintered PTFE filter	1							
	Output Scaling	0...5000 ppm with porous sintered PTFE filter	2							
		0...2000 ppm with porous sintered PTFE filter	3							
		0...3000 ppm with porous sintered PTFE filter	4							
		0...20 000 ppm with porous sintered PTFE filter	5							
Probe options and settings	2 Output mode	RS-485 Modbus	0							
		RS-485 Vaisala protocol / Indigo™ use	1							
		4...20 mA*	2							
		0...20 mA*	3							
		0...5 V*	4							
Probe options and settings	3 Temperature compensation	Temperature setpoint +25 °C**			A					
		Temperature setpoint +37 °C**			B					
		Active internal compensation*** (recommended)			C					
Probe options and settings	4 Pressure compensation	Pressure setpoint 1013 hPa**	0							
	5 Background gas compensations	Background gas setpoint 0 %O2, 0 %RH**			A					
Other options	6 Cable	no cable	0							
		<i>Probe cable with open wires (1.5 m)</i>	1							
		<i>Probe cable with open wires and 90° plug (0.6 m)</i>	3							
		<i>Probe cable with open wires (10 m)</i>	4							
		<i>Probe cable with open wires (3 m)</i>	5							
Other options	7 Mounting	no mounting accessories						N		
		<i>Probe mounting clips (2 pcs)</i>						C		
		<i>Probe mounting flange</i>							F	
Other options	8 Package	Single package	1							
		10 piece multi-package (to use this, order must contain 10 units)	2							

Selections in bold are included in the prices of the basic version.
Selections in italic are available at an extra price.

*) Analog output mode requires grounding of pin 5 (connecting pin 3 and pin 5 together)
**) Compensation setpoint values can be updated via RS485 communications
***) Uses the probe internal temperature sensing, accuracy limited to ±3 °C in typical installation conditions

Examples of order codes with typical settings:

		1	2	3	4	5	6	7	8
Standard CO ₂ Probe for demanding HVAC application	GMP252	2	2	A	0	B	1	C	1

End customer: _____

Accessories

- Porous sintered PTFE filter for GMP252
- Probe cable with open wires (1.5 m)
- Probe cable with open wires and 90° plug (0.6 m)
- Probe cable with open wires (10 m)
- Probe cable with open wires (3 m)
- Probe mounting clips (2 pcs)
- Probe mounting flange
- USB cable for PC connection
- MI70 connection cable for probe
- Flat cable for GMP250 probes, M12-5pin
- Calibration adapter
- Spray Shield (IPX9 Rating)
- Radiation Shield DTR250 with Mast Installation Kit
- Radiation Shield DTR250 for Outdoor Use

Item code

- DRW244221SP
- 223263SP
- 244669SP
- 216546SP
- 26719SP
- 243257SP
- 243261SP
- 242659
- CBL210472
- CBL210493SP
- DRW244827SP
- ASM212017SP
- DTR250A
- DTR250

GMP252 Indigo™ Order Form, please see the next page.

GMP252 Carbon Dioxide Probe for ppm-level measurements For Indigo™ Transmitter

		1	2	3	4	5	6	7	8	PRICE
Vaisala CARBOCAP® Carbon Dioxide Probe		GMP252								
1	Probe type / Analog	0...10 000 ppm with porous sintered PTFE filter								1
	Output Scaling	0...5000 ppm with porous sintered PTFE filter								2
		0...2000 ppm with porous sintered PTFE filter								3
	Indigo transmitter	0...3000 ppm with porous sintered PTFE filter								4
	automatically use this scale on its outputs	0...20 000 ppm with porous sintered PTFE filter								5
2	Output mode	Indigo™ use								1
3	Temperature compensation	Temperature setpoint +25 °C								A
		Temperature setpoint +37 °C								B
		Active internal compensation* (recommended)								C
4	Pressure compensation	Pressure setpoint 1013 hPa								0
5	Background gas compensations	Background gas setpoint 0 %O2, 0 %RH								A
		Background gas setpoint 21 %O2, 50 %RH								B
6	Cable	no cable								0
7	Mounting	no mounting accessories								N
8	Package	Single package								1
		10 piece multi-package (to use this, order must contain 10 units)								2

Selections in bold are included in the prices of the basic version.

Selections in italic are available at an extra price.

*) Uses the probe internal temperature sensing, accuracy limited to ±3 °C in typical installation conditions

Examples of order codes with typical settings:

GMP252 with typical settings: **GMP252** | **2** | **1** | **A** | **0** | **B** | **0** | **N** | **1**

End customer: _____

Accessories

Probe connection cable for Indigo™, 1 m
 Probe connection cable for Indigo™, 3 m
 Probe connection cable for Indigo™, 5 m
 Probe connection cable for Indigo™, 10 m
 Standard membrane filter
 Porous sintered PTFE filter, extra protection
 Flow-through adapter with gas ports
 Probe mounting clips (2 pcs)
 Probe mounting flange
 USB cable for PC connection
 MI70 connection cable for probe
 Flat cable for GMP250 probes, M12-5pin
 Calibration adapter
 Spray Shield (IPX9 Rating)
 Radiation Shield DTR250 with Mast Installation Kit
 Radiation Shield DTR250 for Outdoor Use

Item code

INDIGOCABLE1M
 INDIGOCABLE3M
 INDIGOCABLE5M
 INDIGOCABLE10M
 ASM211650SP
 DRW243649SP
 ASM211697SP
 243257SP
 243261SP
 242659
 CBL210472
 CBL210493SP
 DRW244827SP
 ASM212017SP
 DTR250A
 DTR250

Standard GMP252 Order Form, please see the next page.