

Vaisala HMD60 HMD60 Humidity & Temperature Duct Transmitter

Humidity & Temperature Duct Transmitter		HMD60	1	2	3	4	5	6	7	8	9	10	Price	
1	Probe Length	Standard (25 cm) <i>Short (10cm)</i>	A	B										
2	Output Signal	4 ... 20 mA (loop powered) 0 ... 10 V 0 ... 5 V 1 ... 5 V BACnet/Modbus	1	2	3	4	5							
3	Channel 1	RH (0...100%) Td/f (-40 ...+80°C) A (0 ... 300 g/m³) X (0 ... 600 g/kg) Tw (-40 ... +80°C) H (-40 ... +1600 kJ/kg)	A	B	C	D	E	F	X					
	Special	<i>Define Quantity:</i>	<i>Scale:</i>											
4	Channel 2	T (-20 ...+80°C) T (-40 ...+80°C)	1	2	X									
	Special	<i>Define Quantity:</i>	<i>Scale:</i>											
5	Identity	Vaisala			A									
6	Sensor	Humicap R2				1								
7	Filter	Stainless Steel Grid <i>Sintered Stainless Steel Filter</i> <i>Sintered Teflon Filter</i>			A	B	C							
8	Bushing 1 (small)	Plugged Cable gland 4...8 mm <i>Conduit fitting NPT1/2"</i>								0	1	2		
9	Bushing 2 (large)	Plugged <i>Cable Gland 6...12 mm</i>									N	A		
10	User Guide	None <i>Multilingual Analog</i> <i>Multilingual Digital</i>										0	1	2
												TOTAL		
												QTY		
												TOTAL VALUE		

Additional information

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMD60 A 1 A 1 A 1 A 1 N 1

Spare Parts

Stainless Steel Grid
Sintered Stainless Steel Filter
Sintered Teflon Filter
Cable Gland 4...6 mm
Conduit fitting NPT1/2"

ASM212652SP
HM46670SP
DRW244938SP
254280SP
210675SP