

Vaisala Temperature Probe HMP110T

Vaisala Temperature Probe	HMP110T								PRICE
1 Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4..20 mA converter (channel 1 only) Modbus RS485 Interface for Vaisala devices (VDIGI)	A B C D I M R V							
2 Analog output range	RS485 or VDIGI -40 ... +60°C -40 ... +80°C	0 2 5							
3 Sensor protection	Plastic grid with filter <i>Plastic grid</i> <i>Stainless steel sintered filter</i>	A B C							
	Pair of plastic nuts Probe holder for HMT120/130/140 <i>Duct installation kit</i> 215619					1 2 3			
5 Probe cable length	No cable <i>60 °C cable 0.3 m</i> HMP50Z032 <i>60 °C cable 3 m</i> HMP50Z30A <i>High temperature cable 1.5 m</i> <i>High temperature cable 3 m</i> <i>180 °C FEP cable 3m</i> 226902 <i>180°C FEP cable 1.5m</i> 238025					1 2 3 4 5 F J			
6 User guide	No user guide Multilingual quick guide						A B		
7 Loop power converter	No converter <i>4...20 mA loop power converter</i> Always use single unit package						0 1 2		
TOTAL									
QTY									
TOTAL VALUE									

Selections in bold are included in the prices of the basic versions.
 Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP110T	V	0	B	2	1	A	0
---------	---	---	---	---	---	---	---