

2024-02-28

## HMW92 Humidity and Temperature Transmitters for High Performance Building Automation Applications



### Features/Benefits:

- Uses Vaisala HUMICAP® 180R humidity sensor
- Optional display available for local measurement readout
- Full 0 ... 100 %RH range with accuracy up to  $\pm 1.7$  %RH
- Temperature accuracy up to  $\pm 0.2$  °C
- (2) loop powered, configurable 4 ... 20 mA analog outputs
- Moisture parameters available: Relative humidity, dew point, mixing ratio, enthalpy, wet-bulb temperature, dew point depression, and absolute humidity
- Dip switch configuration for units, parameters, and scaling
- Discrete wiring through back plate
- User exchangeable humidity and temperature modules
- Simplified on site calibration options and adjustment through offset trimmers or PC connection
- Traceable calibration certificate included

### Summary:

Wall mounted transmitter shall incorporate a thin-film polymer capacitive HUMICAP® 180R relative humidity sensor. Transmitter shall be rated for full range of 0 ... 100 %RH with accuracy of  $\pm 1.7$  %RH in the range of 0 ... 90 %RH and  $\pm 2.5$  %RH in the range of 90 ... 100 %RH for temperatures between +10 ... +40 °C (+50 ... +104 °F). Instrument shall be rated for temperatures between -5 ... +55 °C (+23 ... +131 °F) with temperature measurement accuracy of  $\pm 0.2$  °C between +20 ... +30 °C (+68 ... +86 °F). Transmitter to be loop powered by 10 ... 28 VDC ( $R_L = 0 \Omega$ ) or 20 ... 28 VDC ( $R_L = 500 \Omega$ ) and provide a linear output signal of 4 ... 20 mA corresponding to 0 ... 100 %RH. Temperature sensor shall be digital and provide a linear output signal of 4 ... 20 mA corresponding to -5 ... +55 °C (+23 ... +131 °F). Mechanical housing of transmitter shall be rated to IP30. Transmitter shall have the option to calculate and output parameters such as: relative humidity, temperature, dew point, mixing ratio, enthalpy, wet-bulb temperature, dew point depression, and absolute humidity. Transmitter shall have the ability to calibrate relative humidity, without disturbing operation, using a single point electronic field calibrator, or have an interchangeable humidity and temperature module with traceable calibration for easy maintenance. Traceable calibration certificate included. Available models are listed below:

**Vaisala Model:** HMW92 (Relative Humidity and Dry-Bulb Temperature)

**Vaisala Model:** HMW92D (Relative Humidity and Dry-Bulb Temperature with Display)

**Vaisala Model:** TMW92 (Dry-Bulb Temperature Only)

**Note:** *The HMW92 consists of pre-configured models that are a part of the [HMW90 Series](#). The HMW90 Series offers additional pre-configured models, as well as models to be fully configurable (output signals, output parameters, output scaling, etc.).*