



**MMP8 Moisture in Oil Probe**  
With adjustable installation depth

		MMPX	Probe type	Probe type	Probe cable	Sensor type	Filter type	Oil coefficients	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Probe mounting accessory	Connection cable
1	Probe type	MMP8 with adjustable installation depth	8	A	1								
2	Probe cable	Probe 8, 2m	8	A									
3	Sensor type	Humicap L2			1								
4	Filter type	Stainless steel grid filter Stainless steel grid filter for high flow > 1 m/s				A	B						
5	Oil coefficients for ppm calculations 1, 2)	General purpose mineral oil coefficients Midel7131 FR3 Dow Corning 561 Jarylec C101 Rhodosil						0 1 2 3 4 5					
6	Baud rate 1)	19200 use with Indigo transmitter 9600							A B				
7	Parity, data bit, stop bit 1)	8,N,2 use with Indigo transmitter 8,N,1 8,E,1 8,E,2 8,O,1 8,O,2								0 1 2 3 4 5			
8	Probe Modbus address 1)	240 use with Indigo transmitter 110 120 130 140									A B C D E		
9	Reserved	None										0	
10	Probe mounting accessory	Fitting body NPT1/2" Fitting body ISO1/2" <i>Ball Valve installation kit, with welding joint and ISO1/2" fitting body</i> <i>Set: Ballvalve installation kit + NPT1/2" + ISO1/2" fitting bodies</i> <i>Fitting body set ISO 1/2" + NPT 1/2"</i>										item: 212810 item: DRW212076 item: BALLVALVE-1 item: BALLVALVE-1SET item: DRW212076, 212810	C D A E F
11	Connection cable	None 1,5m, open ends 10m, open ends											0 1 2

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)  
Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

2) Irrelevant selection if only Water activity (aw) and Temperature measurements are used.

**Selections in bold are included in the prices of the basic versions.**  
*Selections in italic are available at an extra price.*

**Example of order code with typical settings:**

For use with INDIGO transmitters	MMPX	8	A	1	A	0	A	0	A	0	C	0
For Modbus RTU use	MMPX	8	A	1	A	0	A	0	A	0	C	2

Valid from: November 2022