



Order form
Orderer _____

Valid from April 2021
Order no. _____

MMT330 Moisture and Temperature Transmitter Series for Oil

Vaisala HUMICAP® Moisture and Temperature Transmitter		MMT330	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
1	Transmitter type	MMT332 for pressurized processes with flange MMT337 for tight installations MMT338 for pressurized pipelines	2	7	8																					
2	Probe cable length	2 m cable 5 m cable 10 m cable 2 m cable 5 m cable 10 m cable 20 m cable 2 m cable for 232 mm probe 5 m cable for 232 mm probe 10 m cable for 232 mm probe 2 m cable for 454 mm probe 5 m cable for 454 mm probe 10 m cable for 454 mm probe 15 m cable for 454 mm probe 20 m cable for 454 mm probe	2	7	8	B	C	D	S	T	U	8	V	W	X	1	2	3	5	9						
3	-----	None	0																							
4	Measurement parameters	aw+T aw+T+ppm ppm for mineral transformer oil only %RS + ppm + T ppm for mineral transformer oil only aw+T+ppm specific transformer oil				E	F	G	X																	
5	Display	None Graphical display with keypad	0	1																						
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC -power (100...240 VAC) Universal AC -power (100...240 VAC) + US -power cord Universal AC -power (100...240 VAC) + EUR -power cord Universal AC -power (100...240 VAC) + UK -power cord Universal AC -power (100...240 VAC) + AUS -power cord		1	2	3	4	5	6																	
7	Analog output	4...20 mA 0...20 mA 0...1 V 0...5 V 0...10 V		1	2	3	4	5																		
	Analog output parameter and scaling for Ch1&Ch2(&Ch3)	None T (range: see below) aw (0...1) ppm (0...100) ppm (0...500) %RS (0...100)				C	P	Q	R	R	4	4	4	X												
	SPECIAL	Define parameter (unit) for Ch1: () Ch2: () Optional Ch3: () Define scale for Ch1: Channel 1 Channel 2 Channel 3 (optional), choose A, if not needed				X	X	X																		
8																										
9																										
10																										
11	Analog output range for temperature	None -40...+60°C (-40...+140°F) -40...+80°C (-40...+176°F) NOTE: - Choose option A, if no T output is desired -40...+120°C (-40...+248°F) -40...+180°C (-40...+356°F) -20...+60°C (-4...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -20...+180°C (-4...+356°F) 0...+60°C (+32...+140°F) 0...+100°C (+32...+212°F) 0...+120°C (+32...248°F) 0...+180°C (+32...356°F) -60...60°C (-76...+140°F) special				A	B	C	D	E	F	G	H	I	J	K	L	M	N	P	X					
12	Output units	Metric Non-metric		1	2																					
13	Additional feature	None Relay output RS-485 serial interface (galvanically isolated) Data logging module*)		0	1	2	6																			
14	Additional feature 2	None Relay output 3rd Analog output Data logging module*) Choose also analog output signal for Ch3		0	1	3	6																			
15	Interface cable connection	Cable gland M20*1,5 Conduit fitting NPT1/2" Connector (M12, 8 pin) and plug with 5m cable Connector (M12, 8 pin) and plug (screw terminal)				A	B	C	D																	
16	Transmitter housing installation	Wall Mounting Wall mounting plate (compatible with US junction boxes) Pipe / pole installation Pipe / pole installation with rain shield DIN-rail installation		0	1	2	3	4																		
17	Humidity sensor	Special sensor for fluids																								
18	Sensor protection	Stainless steel grid (standard) Stainless steel grid (for applications with high flow speed, >1 m/s)																								
19	Probe installation accessories	None Swagelok connector NPT 1/2" for MMT337 Swagelok connector ISO 3/8" for MMT337 Swagelok connector ISO 1/2" for MMT337 Ball Valve ISO1/2 with welding joint for MMT338 Pressure fitting NPT1/2 for MMT338 Pressure fitting ISO 1/2 for MMT338 Ball Valve ISO1/2 with thread joint ISO3/4 for MMT338 Ball Valve ISO1/2 with ISO1/2 and NPT1/2 fitting bodies																								
20	User's guide	None English German French Finnish Swedish Chinese Japanese																								
21	PC accessories	None MITOLINK software for Windows® with RS232 service cable Service cable for PC, USB																								
22	Calibration	ISO9001 compliant factory calibration																								
23	Additional maintenance	No maintenance and repair contract																								

*) Choose data logging module only once (option 13 or 14)

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

MMT330

End customer: _____



Order form
Orderer _____

Valid from April 2021
Order no. _____

MMT332 Moisture and Temperature Transmitter for Oil
For High Pressure Applications

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
Vaisala HUMICAP® Moisture and Temperature Transmitter																							
1	Transmitter type	MMT332	2	0																		1	PRICE
2	Probe cable length	2 m cable 5 m cable 10 m cable		B C D																			
3	-----	None		0																			
4	Measurement parameters	aw+T aw+T+ppm %RS + ppm + T aw+T+ppm								E F G X													
5	Display	No display Graphical display with keypad								0 1													
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC -power (100...240 VAC) Universal AC -power (100...240 VAC) + US -power cord Universal AC -power (100...240 VAC) + EUR -power cord Universal AC -power (100...240 VAC) + UK -power cord Universal AC -power (100...240 VAC) + AUS -power cord									0 1 2 3 4 5 6												
7	Analog output	4...20 mA 0...20 mA 0...1 V 0...5 V 0...10 V									1 2 3 4 5												
	Analog output parameter and scaling for Ch1&Ch2(&Ch3)	None T aw (0...1) ppm (0...100) ppm (0...500) %RS																					
	SPECIAL	Define parameter (unit) for Ch1: _____ () Ch2: _____ () Optional Ch3: _____ () Define scale for Ch1: _____ Ch2: _____ Optional Ch3: _____																					
8																							
9																							
10																							
11	Analog output range for temperature	None -40...+60°C -40...+80°C -40...+120°C -40...+180°C -20...+60°C -20...+80°C -20...+120°C -20...+180°C 0...+60°C 0...+100°C 0...+120°C 0...+180°C -60...60 °C																					
	NOTE:	- Choose option A, if no T output is desired																					
	SPECIAL	°C / F																					
12	Output units	Metric Non-metric																					
13	Additional feature	None Relay output RS-485 serial interface (galvanically isolated) Data logging module*)																					
14	Additional feature 2	None Relay output 3rd Analog output Data logging module*)																					
15	Interface cable connection	Cable gland M20*1.5 Conduit fitting NPT1/2" Connector (M12, 8 pin) and plug with 5m cable Connector (M12, 8 pin) and plug (screw terminal)																					
16	Transmitter housing installation	Wall Mounting Wall mounting plate (compatible with US junction boxes) Pipe / pole installation Pipe / pole installation with rain shield DIN-rail installation																					
17	Sensor	Special sensor for fluids																					
18	Sensor protection	Stainless steel grid (standard) Stainless steel grid (for applications with high flow speed, >1 m/s)																					
19	Probe installation access.	None																					
20	User's guide	None English German French Finnish Swedish Chinese Japanese																					
21	PC accessories	None MITOLINK software for Windows® with RS232 service cable Service cable for PC, USB																					
22	Calibration	ISO9001 compliant factory calibration																					
23	-----	None																					

*) Choose data logging module only once (option 13 or 14)

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

MMT330 2 B 0 E 1 2 1 P C A L 1 1 1 A 0 2 D A B A A 1

End customer: _____

TOTAL
QTY
TOTAL VALUE



Order form
Orderer _____

Valid from April 2021
Order no. _____

MMT337 Moisture and Temperature Transmitter for Oil
With Small Pressure-tight Probe

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
Vaisala HUMICAP® Moisture and Temperature Transmitter		MMT330		7	0																	1	
1	Transmitter type	MMT337		7																			
2	Probe cable length	2 m cable 5 m cable 10 m cable 20 m cable		S T U 8																			
3	-----	None		0																			
4	Measurement parameters	aw+T+ppm %RS + ppm + T aw+T+ppm																					
		ppm for mineral transformer oil only ppm for mineral transformer oil only specific transformer oil																					
5	Display	None Graphical display with keypad		0 1																			
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC -power (100...240 VAC) Universal AC -power (100...240 VAC) + US -power cord Universal AC -power (100...240 VAC) + EUR -power cord Universal AC -power (100...240 VAC) + UK -power cord Universal AC -power (100...240 VAC) + AUS -power cord		0 1 2 3 4 5 6																			
7	Analog output	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V		1 2 3 4 5																			
Analog output parameter and scaling for Ch1&Ch2(&Ch3)		No 3rd analog output T (range: see below) aw (0...1) ppm (0...100) ppm (0...500) %RS (0...100)																					
SPECIAL		Define parameter (unit) for Ch1: () Ch2: () Optional Ch3: () Define scale for Ch1: () Ch2: () Optional Ch3: ()																					
8			Channel 1																				
9			Channel 2																				
10			Channel 3 (optional), choose A, if not needed																				
11	Analog output range for temperature	None -40...+60°C (-40...+140°F) -40...+80°C (-40...+176°F) -40...+120°C (-40...+248°F) -40...+180°C (-40...+356°F) -20...+60°C (-4...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -20...+180°C (-4...+356°F) 0...+60°C (+32...+140°F) 0...+100°C (+32...+212°F) 0...+120°C (+32...+248°F) 0...+180°C (+32...+356°F) -60...60 °C (-76...+140°F)																					
NOTE:		- Choose option A, if no T output is desired																					
SPECIAL		°C / F																					
12	Output units	Metric Non-metric		1 2																			
13	Additional feature	None Relay output RS-485 galvanic isolation Data logging module*)		0 1 2 6																			
14	Additional feature 2	None Relay output 3rd Analog output Data logging module*)		0 1 3 6																			
Choose also analog output signal for Ch3																							
15	Interface cable connection	Cable stand (for 8...11mm cable) (for 0.315...0.433 inch cable) Conduit fitting for wire conduit (NPT1/2") Connector (M12, 8 pin) and plug with 5m cable Connector (M12, 8 pin) and plug (screw terminal)																					
		spare cable: 212142 spare connector: 212416																					
16	Transmitter housing installation	Wall Mounting Wall mounting mate (compatible with US junction boxes) Pipe / pole installation Pipe / pole installation with rain shield DIN-rail installation		0 1 2 3 4																			
		item: 214829 item: 215108 item: 215109 item: 215094																					
17	Sensor	Special sensor for fluids																					
18	Sensor protection	Stainless steel grid (standard) Stainless steel grid (for applications with high flow speed, >1 m/s)																					
		spare sensor: HUMICAP180L2 spare: HM47453SP spare: 220752SP																					
19	Probe installation accessories	None Swagelok connector NPT 1/2" Swagelok connector ISO 3/8" Swagelok connector ISO 1/2"																					
		spare: SWG12NPT12 spare: SWG12ISO38 spare: SWG12ISO12																					
20	User's guide	None English German French Finnish Swedish Chinese Japanese																					
		A B C D E F V J																					
21	PC accessories	None MITOLINK software for Windows® with RS232 service cable Service cable for PC, USB																					
		item: 215005 item: 219685																					
22	Calibration	ISO9001 compliant factory calibration																					
23	-----	None																					
		standard service calibration: 223304																					

*) Choose data logging module only once (option 13 or 14)

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

MMT330 7 S 0 E 1 2 1 P C A L 1 1 1 A 0 2 D A B A A 1

End customer: _____



Order form
Orderer _____

Valid from April 2021
Order no. _____

MMT338 Moisture and Temperature Transmitter for Oil
For Pressurized Pipelines

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Vaisala HUMICAP® Humidity and Temperature Transmitter		MMT338	8	0																				
1 Transmitter type	MMT338																							
2 Probe cable length	2 m cable for standard probe 5 m cable for standard probe 10 m cable for standard probe 2 m cable for long probe 5 m cable for long probe 10 m cable for long probe 15 m cable for long probe 20 m cable for long probe	V W X 1 2 3 5 9																						
3	None																							
4 Measurement parameters	aw+T aw+T+ppm ppm for mineral transformer oil only %RS + ppm + T ppm for mineral transformer oil only aw+T+ppm specific transformer oil oil type:	E F G X																						
5 Display	No display Graphical display with keypad	0 1																						
6 Power supply	10...35 VDC 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC -power (100...240 VAC) Universal AC -power (100...240 VAC) + US -power cord Universal AC -power (100...240 VAC) + EUR -power cord Universal AC -power (100...240 VAC) + UK -power cord Universal AC -power (100...240 VAC) + AUS -power cord	0 1 2 3 4 5 6																						
7 Analog output	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V	1 2 3 4 5																						
Analog output parameter and scaling for Ch1&Ch2(&Ch3)	No 3rd analog output T (range: see below) aw (0...1) (0...1) ppm (0...100) (0...100) ppm (0...500) (0...500) %RS (0...100)																							
SPECIAL	Define parameter (unit) for Ch1: _____ Ch2: _____ Optional Ch3: _____ Define scale for Ch1: _____ Ch2: _____ Optional Ch3: _____																							
8																								
9																								
10																								
11 Analog output range for temperature	None -40...+60°C (-40...+140°F) NOTE: -40...+80°C (-40...+176°F) - Choose option A, if no -40...+120°C (-40...+248°F) T output is desired -40...+180°C (-40...+356°F) -20...+60°C (-4...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -20...+180°C (-4...+356°F) 0...+60°C (+32...+140°F) 0...+100°C (+32...+212°F) 0...+120°C (+32...248°F) 0...+180°C (+32...356°F) -60...60 °C (-76...+140°F)	A B C D E F G H J K L M N P X																						
12 Output units	Metric Non-metric	1 2																						
13 Additional feature	None Relay output RS-485 galvanic isolation Data logging module*)	0 1 2 6																						
14 Additional feature 2	None Relay output 3rd Analog output Choose also analog output signal for Ch3 Data logging module*)	0 1 3 6																						
15 Interface cable connection	Cable gland (for 8...11mm cable) Conduit fitting for wire conduit (NPT1/2") Connector (M12, 8 pin) and plug with 5m cable spare cable: 212142 Connector (M12, 8 pin) and plug (screw terminal) spare connector: 212416																							
16 Transmitter housing installation	Wall Mounting Wall mounting plate (compatible with US junction boxes) item: 214829 Pipe / pole installation item: 215108 Pipe / pole installation with rain shield item: 215109 DIN-rail installation item: 215094	0 1 2 3 4																						
17 Sensor	Special sensor for fluids spare sensor: HUMICAP180L2																							
18 Sensor protection	Stainless steel grid (standard) spare: HM47453SP Stainless steel grid (for applications with high flow speed, >1 m/s) spare: 220752SP																							
19 Probe installation accessories	Ball Valve ISO1/2 with welding joint Ball Valve ISO1/2 with thread joint ISO 3/4 Pressure fitting NPT1/2 Pressure fitting ISO 1/2 Ball Valve ISO1/2 with ISO1/2 and NPT1/2 fitting bodies																							
20 User's guide	None English German French Finnish Swedish Chinese Japanese																							
21 PC accessories	None M170LINK software for Windows® with RS232 service cable item: 215005 Service cable for PC, USB item: 219685																							
22 Calibration	ISO9001 compliant factory calibration standard service calibration: 223304																							
23	None																							

*) Choose data logging module only once (option 13 or 14)

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

MMT338 | **8** | **V** | **0** | **E** | **1** | **2** | **1** | **P** | **C** | **A** | **L** | **1** | **1** | **1** | **A** | **0** | **2** | **D** | **M** | **B** | **A** | **A** | **1**

End customer: _____