

## TMI110 Immersion Temperature Transmitter

Vaisala Temperature Transmitter		TMI110	1	2	3	4	5	6	7	8
HW	1 Output Signals	<b>4...20 mA</b>	2							
		<b>Modbus</b>	M							
Settings	2 Measured Parameter for Channel 1	T (0 ... +50°C)	A							
		T (-10 ... +40°C)	B							
		T (-40 ... +60°C)	C							
		T (0 ... +100°C)	D							
	Special Scale, °C	T	X							
	Special Scale, °F	T	Y							
		<b>None (for Modbus)</b>	N							
HW	5 Probe length	<b>100 mm (3.9")</b>	1							

NOTE: Selections in bold are included in the prices of the basic versions.  
 • *Selections in italic are available at an extra price.*

LINKS: [Link to Datasheet: B212427EN](#)  
[Link to User Guide: M211726EN](#)  
[Link to Vaisala.com Product Page](#)

Example of order code with typical settings:

TMI110	2	A	N	V	1	O	N	N
--------	---	---	---	---	---	---	---	---

### Spare Parts and Accessories

Spare Parts and Accessories	Part Number
Thermowell (ISO 7 - R 1/2 thread)	ASM214691
Thermowell (1/2 - 14 NPT thread)	ASM214707
Conduit fitting + O-ring (M16x1.5 / NPT1/2")	210675SP
Conduit fitting + O-ring (M16x1.5/PG9, RE-MS)	210674SP
Terminal block, blue	23662OSP
USB cable for PC connection	219690
Connection cable for HM70 handheld meter	219980SP