



Temperature probe TMP1  
IP68 immersion and steam proof

		Probe type	Probe cable	Sensor type	Filter type	Sensor purge	Baud rate	Parity, Data bit, Stop	Modbus address	Reserved	Installation accessory	Connection cable	
		TMPX	1	2	3	4	5	6	7	8	9	10	11
1	<b>Probe type</b> TMP1 temperature probe, IP68		1										
2	<b>Cable length</b> Probe 1, 2m Probe 1, 10m			A B									
3	<b>Sensor type</b> PT100 (class F0.1 IEC 60751)			1									
4	<b>Filter type</b> None				A								
5	<b>Reserved</b> None					0							
6	<b>Baud rate</b> 1) 19200 9600						A B						
7	<b>Parity, data bit, stop bit</b> 1) 8,N,2 8,E,1 8,O,1							0 2 4					
8	<b>Probe Modbus address</b> 1) 240 110 120 130 140								A B C D E				
9	<b>Reserved</b> None									0			
10	<b>Probe mounting accessory</b> None Duct installation kit Swagelok for ISO 1/8" Swagelok for NPT 1/8"										0 A B C		
11	<b>Connection cable</b> None 1,5m, open ends 10m, open ends											0 1 2	

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

**Selections in bold are included in the prices of the basic versions.**

*Selections in italic are available at an extra price.*

Example of order code with typical settings:

For use with INDIGO transmitters	TMPX	1	A	1	A	0	A	0	A	0	0	0
For use with Modbus RTU	TMPX	1	A	1	A	0	A	0	A	0	0	2

Valid from: September 2020