



Order form
Purchaser

Valid from August 2021
Order no.

TMT130 Temperature Transmitter

| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | Price |
|--|---|--------|---|---|---|---|---|---|---|---|----|----|----|----|-------------|-------|
| Temperature Transmitter | | TMT130 | | | | | | | | | | | | | | |
| Measurement type | Temperature (HMP110T) | A | | | | | | | | | | | | | | |
| Probe details | Wall mount/fix probe HMP110T | A | | | | | | | | | | | | | | |
| | <i>Remote probe with 3 m cable</i> | B | | | | | | | | | | | | | | |
| | <i>Remote probe with 5 m cable</i> | C | | | | | | | | | | | | | | |
| | <i>Remote probe with 10 m cable</i> | D | | | | | | | | | | | | | | |
| | <i>Remote probe with 10 m cable + 10 m extension</i> | E | | | | | | | | | | | | | | |
| | <i>Remote probe with 20 m cable</i> | F | | | | | | | | | | | | | | |
| | <i>Remote probe with 1.2 m cable</i> | G | | | | | | | | | | | | | | |
| Display | No display | 0 | | | | | | | | | | | | | | |
| | <i>Display</i> | 1 | | | | | | | | | | | | | | |
| | <i>No Display, no logo</i> | N | | | | | | | | | | | | | | |
| Analog output signal (RS485 also included) | 0...1 V 3-wire | | B | | | | | | | | | | | | | |
| | 0...5 V 3-wire | | C | | | | | | | | | | | | | |
| | 0...10 V 3-wire | | D | | | | | | | | | | | | | |
| SPECIAL | Define scale: 3-wire _____ V *) | | X | | | | | | | | | | | | | |
| Parameter for Output 1 | T | | B | | | | | | | | | | | | | |
| | -40...+60 °C (-40...+140 °F) | | C | | | | | | | | | | | | | |
| | -20...+80 °C (-4...+176 °F) | | D | | | | | | | | | | | | | |
| | 0...+60 °C (+32...+140 °F) | | E | | | | | | | | | | | | | |
| | -40...+80 °C (-40...+176 °F) | | F | | | | | | | | | | | | | |
| | 0...+50 °C (+32...+122 °F) | | X | | | | | | | | | | | | | |
| SPECIAL | Define quantity _____ Scale _____ | | X | | | | | | | | | | | | | |
| Parameter for Output 2 | None | | A | | | | | | | | | | | | | |
| | | | 0 | | | | | | | | | | | | | |
| Display Units | Metric | | | | | | | | | 1 | | | | | | |
| | Non metric | | | | | | | | | 2 | | | | | | |
| Sensor protection | Plastic grid (for HMP110T) | | | | | | | | | | | | | | | 1 |
| | Plastic grid with PTFE filter (for HMP110T) | | | | | | | | | | | | | | | 2 |
| | <i>Stainless steel sintered filter (for remote probes of HMP110T only)</i> | | | | | | | | | | | | | | | 3 |
| | <i>Teflon sintered filter for HMP110T DRW244938SP</i> | | | | | | | | | | | | | | | E |
| Transmitter installation | No accessories | | | | | | | | | | | | | | | A |
| | <i>Rain shield with installation kit (215109)</i> | | | | | | | | | | | | | | | C |
| Installation kit for probe | No accessories | | | | | | | | | | | | | | | 1 |
| | <i>Duct installation kit (215619)</i> | | | | | | | | | | | | | | | 2 |
| | <i>Probe mounting flange (226061)</i> | | | | | | | | | | | | | | | 3 |
| | <i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i> | | | | | | | | | | | | | | | 5 |
| | <i>Probe mounting clamp, 1 piece (225501)</i> | | | | | | | | | | | | | | | 6 |
| Cable bushings | Cable gland for 2...6 mm diameter cable | | | | | | | | | | | | | | | A |
| | <i>Conduit fitting PG9</i> | | | | | | | | | | | | | | | B |
| | <i>Conduit fitting NPT 1/2"</i> | | | | | | | | | | | | | | | C |
| | No bushing (rubber plug) | | | | | | | | | | | | | | | D |
| | <i>All bushings (includes A, B, C and D)</i> | | | | | | | | | | | | | | | Z |
| PC Accessories | No | | | | | | | | | | | | | | | 0 |
| | <i>Service cable for PC, USB (219685)</i> | | | | | | | | | | | | | | | 1 |
| Operation manual | No manual | | | | | | | | | | | | | | | A |
| | Multilingual | | | | | | | | | | | | | | | Z |
| | | | | | | | | | | | | | | | Total | |
| | | | | | | | | | | | | | | | QTY | |
| | | | | | | | | | | | | | | | Total value | |

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions

Selections in italic are available at an extra cost

Example of order code with typical settings

TMT130 A A 1 D B A 0 1 1 A 1 A 0 Z