

## Vaisala Radiosonde RS41-SGP

### RS41 PTU Sensors

The Vaisala Radiosonde RS41 temperature sensor utilizes linear resistive platinum technology and is very stable. The small size of the sensor results in low solar radiation error and guarantees fast response. It also incorporates effective protection against evaporating cooling, a phenomenon occasionally encountered when a radiosonde emerges from a cloud top.

The humidity sensor integrates humidity and temperature sensing elements. Pre-flight automatic reconditioning of the humidity sensor effectively removes chemical contaminants and ensures excellent humidity measurement accuracy. The integrated temperature sensor is used to compensate the effects of solar radiation in real time. The sensor heating function enables an active and effective de-icing method at freezing conditions during the flight. The humidity sensor also responds quickly to detect fine structures of the atmosphere.

The pressure sensor is the same high-quality, shock-resistant capacitive silicon sensor as the one in the Vaisala Radiosonde RS92 with revised electronics and calibration.

All the RS41 sensors are calibrated against references that are traceable to international standards (SI units) and measurement uncertainties are estimated according to recommendations of the Joint Committee for Guides in Metrology, 100:2008.

### Carrying Out Ground Checks on a RS41 Radiosonde

Radiosonde preparation involves several steps, including sensor functionality checks and setting the desired options for in-flight operational parameters, like timer to power off the radiosonde at the desired time, pressure, or altitude. During the preparation procedure the operator can also set the transmitter frequency of the radiosonde or apply the station default frequency.

The ground check device is conveniently operated with Vaisala MW41 software. A short-range wireless communication link is used for powering on the radiosonde and for data transfer during the ground check.

The in-built temperature sensor check includes a comparison of readings from the temperature element of the humidity sensor and the actual temperature sensor, although no correction to radiosonde measurement is applied.

With the new humidity sensor design, the radiosonde is able to generate physical zero humidity reference more consistently than is possible with desiccants. The sensor can measure the deviation of humidity measurement at physical zero (0 %RH) and fine-tune the humidity measurement accordingly.

For the pressure measurement ground check, the sounding software MW41 displays the RS41 pressure sensor reading difference against an optional barometer module installed inside the ground check device, and adjusts the measurement accordingly. Alternatively an external precision barometer can be used as the reference value and the readings entered manually.

### Wind Data and GPS-Based Height and Pressure Measurements

Wind, as well as height and pressure readings are derived from velocity and location measurements of the RS41 GPS receiver. Wind is calculated independently based on satellite carrier frequency changes. With RS41-SGP height and pressure are also calculated from satellite ranging codes, combined with differential corrections from the MW41 ground station, as with RS41-SG.

### Data Transmission

The Vaisala Radiosonde RS41 has a proven data transmission range from radiosonde to receiver of up to 350 km. Data availability during a sounding is guaranteed with digital error-correction code transmission, and telemetry errors are always detected. Due to narrower band transmission, more channels are available in the meteorological frequency band.

### Operational Benefits

The RS41's robust and compact design makes it easy to handle and there is no assembly needed prior to launch. The status LED indicates when the radiosonde



*Vaisala Radiosonde RS41-SGP – accuracy and reliability.*

### Benefits

- Superior PTU measurement performance with a pressure sensor
- Automated ground check
- Robust and easy-to-use
- GPS for continuous wind data availability as well as additional height and pressure calculation
- Stable narrow-band transmission complies with ETSI standard EN 302 054

is ready to launch, and if there is an error, it is clearly indicated prior to launch. With the unwinder the radiosonde sensor boom is automatically and consistently set in an ideal position for sounding.

### Add-On Sensor Connector

The RS41 has an interface for additional sensors, primarily to connect it to the ozone interface OIF411. Other sensors with Xdata protocol can also be connected. The data is transferred either directly or via a OIF411 interface to a RS41 radiosonde and onward to the Vaisala DigiCORA® Sounding System MW41.

# Technical Data

## Measurements

Measurement cycle 1 s

TEMPERATURE SENSOR TYPE: PLATINUM RESISTOR  
 Measurement range +60 °C to -90 °C  
 Resolution 0.01 °C  
 Response time (63.2%, 6 m/s flow, 1000 hPa)<sup>1)</sup> 0.5 s  
 Stability (1 year / 3 years) < 0.05 °C / < 0.1 °C  
 Accuracy (Repeatability & Combined uncertainty with k=2)  
 Repeatability in calibration 0.1 °C  
 Combined uncertainty after ground preparation 0.2 °C  
 Combined uncertainty in sounding < 16 km 0.3 °C  
 Combined uncertainty in sounding > 16 km 0.4 °C  
 Reproducibility in sounding > 100 hPa<sup>2)</sup> 0.15 °C  
 < 100 hPa<sup>2)</sup> 0.30 °C

HUMIDITY SENSOR TYPE: THIN-FILM CAPACITOR  
 Measurement range 0 to 100 %RH  
 Resolution 0.1 %RH  
 Response time  
 6 m/s, 1000 hPa, +20 °C < 0.3 s  
 6 m/s, 1000 hPa, -40 °C < 10 s  
 Accuracy (Repeatability & Combined uncertainty with k=2)  
 Repeatability in calibration 2 %RH  
 Combined uncertainty after ground preparation 3 %RH  
 Combined uncertainty in sounding 4 %RH  
 Reproducibility in sounding<sup>2)</sup> 2 %RH

PRESSURE TYPE: SILICON CAPACITOR  
 Measurement range from surface pressure to 3 hPa  
 Resolution 0.01 hPa  
 Accuracy (Repeatability & Combined uncertainty with k=2)  
 Repeatability in calibration  
 > 100 hPa 0.4 hPa  
 100 - 3 hPa 0.3 hPa  
 Combined uncertainty in sounding  
 > 100 hPa 1.0 hPa  
 100 - 3 hPa 0.6 hPa  
 Reproducibility in sounding<sup>2)</sup>  
 > 100 hPa 0.5 hPa  
 100 - 3 hPa 0.3 hPa

WIND SPEED  
 Velocity measurement uncertainty<sup>4)</sup> 0.15 m/s  
 Resolution 0.1 m/s  
 Maximum reported wind speed<sup>3)</sup> 160 m/s

WIND DIRECTION  
 Directional measurement uncertainty<sup>4)</sup> 2 deg  
 Resolution 0.1 deg  
 Wind direction range 0 to 360 deg

## Telemetry

Transmitter type Synthesized  
 Frequency band 400.15 – 406 MHz  
 Tuning range 400.16 – 405.99 MHz  
 Maximum transmitting range up to 350 km  
 Frequency stability, 90 % probability ± 2 kHz  
 Deviation, peak-to-peak 4.8 kHz  
 Emission bandwidth According to EN 302 054  
 Output power (high-power mode) min. 60 mW  
 Sideband radiation According to EN 302 054  
 Modulation GFSK  
 Data downlink 4800 bit/s  
 Frequency setting Wireless with ground check device

## GPS receiver (SA Off, PDOP<4)

Number of channels ≥ 48  
 Frequency 1575.42 MHz, L1 C/A code  
 Cold Start Acquisition Time 35 s (nominal)  
 Reacquisition Time 1 s (nominal)  
 Correction Differential  
 Reporting resolution of lat, lon position values 1e-8°

## Operational Data

Power-up Wireless with ground check device or with switch  
 Factory calibration Stored on Flash memory  
 Battery 2 pcs AA-size Lithium cells  
 Operating time > 240 min  
 Weight EPS/plastic covers 84 g / 113 g  
 Dimensions<sup>5)</sup> Body (L x W x H): 155 x 63 x 46 mm  
 Sensor boom bent (L x W x H): 282 x 63 x 104 mm

## Add-On Sensor Support

Protocol support Xdata to connect several sensors in the same chain, data transferred either directly or via OIF411 to RS41  
 Transfer rate max. 200 bytes/s

## Unwinder

Material of the string Non-UV treated polypropylene  
 Tenacity < 115 N  
 Length of the string 55 m  
 Unwinding speed 0.35 m/s  
 Weight 25 g

The performance data is expressed with 2-sigma confidence level (k=2), unless otherwise explicitly specified.  
 For humidity, the performance data is valid T > -60 °C.

- 1) After applying time-lag correction, the effect to measurement uncertainty is negligible.
- 2) Standard deviation of differences in twin soundings, ascent rate above 3 m/s for temperature and humidity
- 3) In practice unlimited
- 4) Standard deviation of differences in twin soundings. Wind speed above 3 m/s for directional measurement uncertainty.
- 5) For EPS cover, without wire antenna

**VAISALA**

Please contact us at  
[www.vaisala.com/requestinfo](http://www.vaisala.com/requestinfo)



Scan the code for more information

Ref. B211444EN-E ©Vaisala 2017  
 This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

[www.vaisala.com](http://www.vaisala.com)

