



HMT120温度变送器

| Vaisala温度变送器 |                               | HMT120       |                 | T |   | A | A |   |   |   |   |   |   |  |  |  |   | 价格 |
|--------------|-------------------------------|--------------|-----------------|---|---|---|---|---|---|---|---|---|---|--|--|--|---|----|
| 1 输出参数       | 温度                            |              |                 | T |   |   |   |   |   |   |   |   |   |  |  |  |   |    |
| 2 变送器类型      | 墙面安装式/固定探头                    |              |                 |   | A |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 远程探头, 带3米电缆                   |              |                 |   | B |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 远程探头, 带5米电缆                   |              |                 |   | C |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 远程探头, 带10米电缆                  |              |                 |   | D |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 远程探头, 带10米电缆+10米延长            |              |                 |   | E |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 远程探头, 带20米电缆                  |              |                 |   | F |   |   |   |   |   |   |   |   |  |  |  |   |    |
| 3 显示         | 无显示                           |              |                 | 0 |   |   |   |   |   |   |   |   |   |  |  |  |   |    |
|              | 有显示                           |              |                 | 1 |   |   |   |   |   |   |   |   |   |  |  |  |   |    |
| 4 信号输出       | 4...20 mA                     | 两线制回路供电      |                 |   |   | A |   |   |   |   |   |   |   |  |  |  |   |    |
| 5 通道1输出参数    | 温度                            | -40...+60 °C | (-40...+140 °F) |   |   |   | B |   |   |   |   |   |   |  |  |  |   |    |
|              |                               | -20...+80 °C | (-4...+176 °F)  |   |   |   | C |   |   |   |   |   |   |  |  |  |   |    |
|              |                               | 0...+60 °C   | (+32...+140 °F) |   |   |   | D |   |   |   |   |   |   |  |  |  |   |    |
|              |                               | -40...+80 °C | (-40...+176 °F) |   |   |   | E |   |   |   |   |   |   |  |  |  |   |    |
| 特殊           | 参数                            | 0...+50 °C   | (+32...+122 °F) |   |   |   | F |   |   |   |   |   |   |  |  |  |   |    |
|              |                               | T            | 量程              |   |   |   | X |   |   |   |   |   |   |  |  |  |   |    |
| 6 通道2输出参数    | 无                             |              |                 |   |   |   | A |   |   |   |   |   |   |  |  |  |   |    |
| 7 显示单位       | 公制                            |              |                 |   |   |   |   | 1 |   |   |   |   |   |  |  |  |   |    |
|              | 非公制                           |              |                 |   |   |   |   | 2 |   |   |   |   |   |  |  |  |   |    |
| 8 传感器保护      | 塑料格栅                          |              |                 |   |   |   |   |   | 1 |   |   |   |   |  |  |  |   |    |
|              | 塑料格栅, 带PTFE过滤器                |              |                 |   |   |   |   |   | 2 |   |   |   |   |  |  |  |   |    |
|              | 不锈钢烧结过滤器 (只适用于远程探头)           |              |                 |   |   |   |   |   | 3 |   |   |   |   |  |  |  |   |    |
|              | 特氟龙烧结过滤器                      |              | DRW244938SP     |   |   |   |   |   | E |   |   |   |   |  |  |  |   |    |
| 9 变送器安装件     | 无                             |              |                 |   |   |   |   |   |   | A |   |   |   |  |  |  |   |    |
|              | 带防雨罩的安装背板 (215109)            |              |                 |   |   |   |   |   |   | C |   |   |   |  |  |  |   |    |
| 10 探头安装组件    | 无                             |              |                 |   |   |   |   |   |   |   | 1 |   |   |  |  |  |   |    |
|              | 管道安装件 (215619)                |              |                 |   |   |   |   |   |   |   | 2 |   |   |  |  |  |   |    |
|              | 探头安装法兰 (226061)               |              |                 |   |   |   |   |   |   |   | 3 |   |   |  |  |  |   |    |
|              | 室外安装: DTR504A 防辐射罩 (DTR504A)  |              |                 |   |   |   |   |   |   |   | 5 |   |   |  |  |  |   |    |
|              | 探头安装夹, 1个 (225501)            |              |                 |   |   |   |   |   |   |   | 6 |   |   |  |  |  |   |    |
| 11 电缆套件      | 密封式电缆套(gland), 适用2...6 mm直径电缆 |              |                 |   |   |   |   |   |   |   |   | A |   |  |  |  |   |    |
|              | 管道式电缆套 PG9                    |              |                 |   |   |   |   |   |   |   |   | B |   |  |  |  |   |    |
|              | 管道式电缆套 NPT 1/2"               |              |                 |   |   |   |   |   |   |   |   | C |   |  |  |  |   |    |
|              | 无电缆套 (橡胶塞)                    |              |                 |   |   |   |   |   |   |   |   | D |   |  |  |  |   |    |
|              | 上述各种套件 (包含A, B, C and D)      |              |                 |   |   |   |   |   |   |   |   | Z |   |  |  |  |   |    |
| 12 与PC机连接附件  | 无                             |              |                 |   |   |   |   |   |   |   |   |   | 0 |  |  |  |   |    |
|              | 与PC机连接的服务电缆, USB接口 (219685)   |              |                 |   |   |   |   |   |   |   |   |   | 1 |  |  |  |   |    |
| 13 操作手册      | 无                             |              |                 |   |   |   |   |   |   |   |   |   |   |  |  |  | A |    |
|              | 多语种手册                         |              |                 |   |   |   |   |   |   |   |   |   |   |  |  |  | Z |    |

单价  
数量  
总价

粗体字的选型已包括在基本价格中, 斜体字的选项要附加价格  
此选型表由英文版本翻译而得, 如有不妥之处, 敬请参照英文选型表

典型选型

|        |   |   |   |   |   |   |   |   |   |   |   |   |   |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|---|
| HMT120 | T | A | 0 | A | B | A | 1 | 1 | A | 1 | A | 0 | Z |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|---|